





































## CABINS AND DOORS

	TYPE	SERIES	DESCRIPTION	SECURITY LEVEL (according to the configuration)	SIZE (mm)	FREE PASSAGE AREA	WEIGHT ca. (Kg; standard version)	DEMONTABLE	THROUGHPUT ca. (max with single presence control where applicable and std. glass)	GLASS	MANUAL LOCK	COLLAPSING WINGS	METAL DETECTOR	SINGLE PRESENCE	LEFT OBJECT	ANTI-PASSBACK FUNCTION	TRANSIT TYPE	INSTALLATION AND START UP PERIOD (in the basic configuration)	DELIVERY TIME (starting from the order confirmation, exworks Tonali Spa - Arluno MI)	OTHER FEATURES	APPLICATIONS
<b>SECURITY CABINS</b>																					
TOP 150 	TOP 150	474	Automatic square cabin 180°, 90° right, 90° left	high	1050 x 1050 x H 2222	580 x H 2000	700	NA	4-5 cycles one-way; 7-8 cycles two ways	STANDARD: BR3/S-P6B (available up to BR4/S-P8B)	available	/	available	available with volumetric control	available	available		INSTAL.: 3h, 2 people START UP: 3h, 1 pers.	from 30 up to 40 useful days	20mm thick floor without necessity to crate it, slope finish	BANKS, AIRPORTS, MINISTRIES, INDUSTRIES
	TOP 150 Plus	475	Automatic square cabin 180°, 90° right, 90° left	high	1150 x 1150 x H 2222	700 x H 2000	850	NA	4-5 cycles one-way; 7-8 cycles two ways	STANDARD: BR3/S-P6B (available up to BR4/S-P8B)	available	/	available	available with volumetric control	available	available		INSTAL.: 3h, 2 people START UP: 3h, 1 pers.	from 30 up to 40 useful days	20mm thick floor without necessity to crate it, slope finish	BANKS, AIRPORTS, MINISTRIES, INDUSTRIES
EM24K 	EM24K	484	Automatic square cabin 180°, 90° right, 90° left	high	1050 x 1050 x H 2222	580 x H 2000	700	DEMONTABLE	4-5 cycles one-way; 7-8 cycles two ways	STANDARD: BR3/S-P6B (available up to BR4/S-P8B)	available	/	available	available with volumetric control	available	available		INSTAL. (assemb): 3h, 2 people INSTAL. (in parts): 4h, 2 people START UP (assemb): 3h, 1 pers. START UP (in parts): 4h, 1 pers.	from 30 up to 60 useful days	20mm thick floor without necessity to crate it, slope finish	BANKS, AIRPORTS, MINISTRIES, INDUSTRIES
	EM24K Plus	493	Automatic square cabin 180°, 90° right, 90° left	high	1150 x 1150 x H 2222	700 x H 2000	850	DEMONTABLE	4-5 cycles one-way; 7-8 cycles two ways	STANDARD: BR3/S-P6B (available up to BR4/S-P8B)	available	/	available	available with volumetric control	available	available		INSTAL. (assemb): 3h, 2 people INSTAL. (in parts): 4h, 2 people START UP (assemb): 3h, 1 pers. START UP (in parts): 4h, 1 pers.	from 30 up to 60 useful days	20mm thick floor without necessity to crate it, slope finish	BANKS, AIRPORTS, MINISTRIES, INDUSTRIES
	EM24K Maxi	494	Automatic square cabin 180°, 90° right, 90° left	medium	1500 x 1500 x H 2222	900 x H 2000	950	DEMONTABLE	3-4 cycles one-way; 6-7 cycles two ways	STANDARD: BR2/S-P6B	available	/	available	available with volumetric control	available	available		INSTAL. (assemb): 4h, 2 people INSTAL. (in parts): 4h, 2 people START UP (assemb): 3h, 1 pers. START UP (in parts): 4h, 1 pers.	da 60 a 90 gg lavorativi	20mm thick floor without necessity to crate it, slope finish	HOSPITALS, BANKS, AIRPORTS, MINISTRIES, INDUSTRIES
TONDA LIGHT K 	TONDA LIGHT K	497	Automatic round 180°	high	Ø 1050 x H 2227	580 x H 2005	450	DEMONTABLE	5-6 cycles one-way; 8-9 cycles two ways	STANDARD: P3A for sliding doors and BR2/S-P6B on sides (available up to BR3/S-P6B)	available	/	available	available with volumetric control	available	available		INSTAL. (assemb): 3h, 2 people INSTAL. (in parts): 4h, 2 people START UP (assemb): 3h, 1 pers. START UP (in parts): 4h, 1 pers.	from 30 up to 60 useful days	20mm thick floor without necessity to crate it, slope finish	BANKS, MINISTRIES, JEWELLER'S SHOP, OFFICES, INDUSTRIES
	TONDA LIGHT K Plus	498	Automatic round 180°	medium	Ø 1150 x H 2267	700 x H 2045	550	DEMONTABLE	4-5 cycles one-way; 7-8 cycles two ways	STANDARD: P3A for sliding doors and BR2/S-P6B on sides (available up to BR2/S-P6B on sliding doors)	available	/	available	available with volumetric control	available	available		INSTAL. (assemb): 3h, 2 people INSTAL. (in parts): 4h, 2 people START UP (assemb): 3h, 1 pers. START UP (in parts): 4h, 1 pers.	from 30 up to 60 useful days	20mm thick floor without necessity to crate it, slope finish	BANKS, MINISTRIES, JEWELLER'S SHOP, OFFICES, INDUSTRIES
	TONDA LIGHT K Maxi	496	Automatic round 180°	medium	Ø 1485 x H 2304	900 x H 2090	750	DEMONTABLE	3-4 cycles one-way; 6-7 cycles two ways	STANDARD: P3A for sliding doors and BR2/S-P6B on sides (available up to BR2/S-P6B on sliding doors)	available	/	available	available with volumetric control	available	available		INSTAL. (assemb): 4h, 2 people INSTAL. (in parts): 6h, 2 people START UP (assemb): 3h, 1 pers. START UP (in parts): 4h, 1 pers.	from 60 up to 90 useful days	12mm thick floor without necessity to crate it, slope finish	BANKS, MINISTRIES, JEWELLER'S SHOP, OFFICES, INDUSTRIES
MULTIWAY 	MULTIWAY 90-90	656	Automatic square cabin with 2 independent corridors 180°	medium	2500 x 1600 x H 2435	2 corridors with 900 x H 2090	1600	ONLY IN PARTS	11-12 cycles one-way; 23-24 cycles two ways	STANDARD: BR2/S-P6B	available	/	available	available with volumetric control	available	available		INSTAL.: 10h, 3 people START UP: 8h, 1 pers.	from 60 up to 90 useful days	20mm thick floor without necessity to crate it, slope finish	BANKS, COURTS, PUBLIC OFFICES, MINISTRIES, INDUSTRIES
UNIVERS 3T 	UNIVERS 3T	106	Automatic round cabin, 3 sectors revolver with additional automatic closing door and M.D.	medium	Ø 1720 x H 2510	700 x H 2090	NA	NA	11-12 cycles one-way; 23-24 cycles two ways	STANDARD: BR2/S-P6B	NA	NA	YES	NA	NA	NA		on request	on request	50mm thick floor	BANKS, PRISONS, COURTS, MINISTRIES


















## CABINS AND DOORS

	TYPE	SERIES	DESCRIPTION	SECURITY LEVEL (according to the configuration)	SIZE (mm)	FREE PASSAGE AREA	WEIGHT ca. (Kg; standard version)	DEMONTABLE	THROUGHPUT ca. (max with single presence control where applicable and std. glass)	GLASS	MANUAL LOCK	COLLAPSING WINGS	METAL DETECTOR	SINGLE PRESENCE	LEFT OBJECT	ANTI-PASSBACK FUNCTION	TRANSIT TYPE	INSTALLATION AND START UP PERIOD (in the basic configuration)	DELIVERY TIME (starting from the order confirmation, exworks Tonali Spa - Arluno MI)	OTHER FEATURES	APPLICATIONS	
<b>ACCESS CONTROL CABINS</b>																						
DUETTO		DUETTO AC	464	Automatic round cabin with two half doors each side 180°	low	Ø 1050 x H 2227	580 x H 2005	450	DEMONTABLE	6-7 cycles one-way; 9-10 cycles two-ways	STANDARD: 8/9mm for sliding doors and BR2/S-P6B on sides	available	/	NA	available with volumetric control	NA	available		INSTAL. (assemb): 3h, 2 people INSTAL. (in parts): 4h, 2 people START UP (assemb): 3h, 1 pers. START UP (in parts): 4h, 1 pers.	from 30 up to 60 useful days	20mm thick floor without necessarily to crate it, slope finish	BUILDING, OFFICES, INDUSTRIES
		DUETTO AC MIDI	465	Automatic round cabin with two half doors each side 180°	medium	Ø 1485 x H 2304	900 x H 2090	750	DEMONTABLE	5-6 cycles one-way; 8-9 cycles two-ways	STANDARD: P3A for sliding doors and BR2/S-P6B on sides (available up to BR2/S-P6B on sliding doors)	available	/	NA	available with volumetric control	NA	available		INSTAL. (assemb): 4h, 2 people INSTAL. (in parts): 6h, 2 people START UP (assemb): 3h, 1 pers. START UP (in parts): 4h, 1 pers.	from 60 up to 90 useful days	20mm thick floor without necessarily to crate it, slope finish	BUILDING, OFFICES, INDUSTRIES, HOSPITALS
		DUETTO MIDI ELLISSE	489	Bussola "tonda allungata" automatica con doppie ante 180°	medio	1450x1900xH2292 Adjustable length: 1900 (standard), 2500 and from 2500 to 4000mm according to the request	900xH2090	850	ONLY IN PARTS	5-6 cycles one-way; 8-9 cycles two-ways	STANDARD: P3A for sliding doors and BR2/S-P6B on sides (available up to BR2/S-P6B on sliding doors)	available	/	NA	available with volumetric control (up to L 2500mm)	available (up to L 2500mm)	available		INSTAL.: 6h, 2 people START UP: 4h, 1 person	from 60 up to 90 useful days	no floor; third swing door available; extendible	BANKS, AIRPORTS, BUILDINGS, POST OFF., INDUSTRIES, HOSPITALS
100TH and MULTITRANSITO		1001H	659	Automatic square cabin with telescopic sliding doors 180°	medium	1600 x 1600 x H 2400	900 x 2050	1200	ONLY IN PARTS	5-6 cycles one-way; 7-8 cycles two-ways	STANDARD: BR2/S-P6B (available up to BR3/S-P6B)	available	/	NA	available with weight cells	NA	available		INSTAL.: 8h, 3 people START UP: 6h, 1 pers.	from 60 up to 90 useful days	20mm thick floor without necessarily to crate it, slope finish	BANKS, COURTS, PUBLIC OFFICES, MINISTRIES, POST OFF., INDUSTRIES
		MULTITRANSITO 70-70	677	Automatic square cabin with 2 independent corridors 180°	medium	2000 x 1600 x H 2400	2 corridors with 700 x H 2050	1400	ONLY IN PARTS	11-12 cycles one-way; 23-24 cycles two-ways	STANDARD: BR2/S-P6B (available up to BR3/S-P6B)	available	/	NA	available with weight cells	NA	available		on request	on request	20mm thick floor without necessarily to crate it, slope finish	BANKS, COURTS, PUBLIC OFFICES, MINISTRIES, POST OFF., INDUSTRIES
		MULTITRANSITO 70-90	657	Automatic square cabin with 2 independent corridors 180°	medium	2300 x 1600 x H 2400	1 corridor with 700 x H 2050 and 1 corridor with 900 x H 2050	1500	ONLY IN PARTS	11-12 cycles one-way; 23-24 cycles two-ways	STANDARD: BR2/S-P6B (available up to BR3/S-P6B)	available	/	NA	available with weight cells	NA	available		INSTAL.: 10h, 3 people START UP: 8h, 1 pers.	from 60 up to 90 useful days	20mm thick floor without necessarily to crate it, slope finish	BANKS, COURTS, PUBLIC OFFICES, MINISTRIES, POST OFF., INDUSTRIES
		MULTITRANSITO 90-90	699	Automatic square cabin with 2 independent corridors 180°	medium	2500 x 1600 x H 2400	2 corridors with 900 x H 2050	1600	ONLY IN PARTS	11-12 cycles one-way; 23-24 cycles two-ways	STANDARD: BR2/S-P6B (available up to BR3/S-P6B)	available	/	NA	available with weight cells	NA	available		on request	on request	20mm thick floor without necessarily to crate it, slope finish	BANKS, COURTS, PUBLIC OFFICES, MINISTRIES, POST OFF., INDUSTRIES
REVOLVING MA		REVOLVING MA 1800	519	Automatic round revolving door with 3 sectors 180°	medium	Ø 1800 x H 2292	750 x H 2090	850	ONLY IN PARTS	14-15 cycles one-way; 29-30 cycles two-ways	STANDARD: P3A (available up to BR2/S-P6B)	available	available	NA	available with ONLYONE PRO	NA	available		INSTAL.: 8h, 2 people START UP: 6h, 1 pers.	from 60 up to 90 useful days	no floor	HOTELS, PUBLIC OFFICES, BUILDINGS
		REVOLVING MA 2300	520	Automatic round revolving door with 4 sectors 180°	medium	Ø 2300 x H 2292	1400 x H 2090	1000	ONLY IN PARTS	19-20 cycles one-way; 39-40 cycles two-ways	STANDARD: P3A (available up to BR2/S-P6B)	available	available	NA	available with ONLYONE PRO	NA	available		INSTAL.: 9h, 2 people START UP: 7h, 1 pers.	from 60 up to 90 useful days	no floor	HOTELS, PUBLIC OFFICES, BUILDINGS
UNIVERS AC		UNIVERS AC	528	Automatic round revolving door with 3 sectors with additional sliding doors 180°	medium	Ø 1800 x H 2292	750 x H 2090	1000	ONLY IN PARTS	11-12 cycles one-way; 23-24 cycles two-ways	STANDARD: P3A (available up to BR2/S-P6B)	available	NA	NA	available with ONLYONE PRO	NA	available		INSTAL.: 10h, 2 people START UP: 9h, 1 pers.	from 60 up to 90 useful days	no floor	AIPORTS, DEPARTMENTS OF JUSTICE, COURTS, PUBLIC OFFICES, BUILDINGS
		UNIVERS AC Maxi	529	Automatic round revolving door with 4 sectors with additional sliding doors 180°	medium	Ø 2300 x H 2292	1050 x H 2090	1300	ONLY IN PARTS	17-18 cycles one-way; 35-36 cycles two-ways	STANDARD: P3A (available up to BR2/S-P6B)	available	NA	NA	available with ONLYONE PRO	NA	available		INSTAL.: 10h, 2 people START UP: 9h, 1 pers.	from 60 up to 90 useful days	no floor	AIPORTS, DEPARTMENTS OF JUSTICE, COURTS, PUBLIC OFFICES, BUILDINGS
<b>BUGLAR RESISTANT CABINS</b>																						
FILTRO BIOMETRICO		FILTRO BIOMETRICO	459	Semi automatic semiround cabin, 60°right, 60°left	very high	1250 x 1000 x H 2400	800 x H2000	825	NA	NA	STANDARD: BR3/S-P6B (available up to BR4/S-P8B)	available	/	NA	available with volumetric control or weight cells	NA	available		INSTAL.: 4h, 2 people START UP: 3h, 1 pers.	from 30 up to 60 useful days	to be used like an emergency exit: 37mm thick floor without necessarily to crate it	HIGH SECURITY VAULT ROOMS, POST OFFICES, BANKS, SUPERMARKETS, SURVEILLANCE DEPARTMENTS
		FILTRO BIOMETRICO LIGHT	467	Semi automatic semiround cabin, 60°right, 60°left	very high	1250 x 1000 x H 2400	800 x H2000	825	NA	NA	STANDARD: BR3/S-P6B (available up to BR4/S-P8B)	available	/	NA	available with volumetric control or weight cells	NA	available		INSTAL.: 4h, 2 people START UP: 3h, 1 pers.	from 60 up to 90 useful days	to be used like an emergency exit: 37mm thick floor without necessarily to crate it	HIGH SECURITY VAULT ROOMS, POST OFFICES, BANKS, SUPERMARKETS, SURVEILLANCE DEPARTMENTS



## CABINS AND DOORS

	TYPE	SERIES	DESCRIPTION	SECURITY LEVEL (according to the configuration)	SIZE (mm)	FREE PASSAGE AREA	WEIGHT ca. (Kg; standard version)	DEMONTABLE	THROUGHPUT ca. (max with single presence control where applicable and std. glass)	GLASS	MANUAL LOCK	COLLAPSING WINGS	METAL DETECTOR	SINGLE PRESENCE	LEFT OBJECT	ANTI-PASSBACK FUNCTION	TRANSIT TYPE	INSTALLATION AND START UP PERIOD (in the basic configuration)	DELIVERY TIME (starting from the order confirmation, exworks Tonalì Spa - Arluno MI)	OTHER FEATURES	APPLICATIONS	
<b>ANTITERRORISM CABINS</b>																						
NO RADIO		noRADIO	471	Automatic square cabin 180°, 90° right, 90° left	very high	1050 x 1050 x H 2222	580 x H 2000	700	DEMONTABLE	4-5 cycles one-way; 7-8 cycles two ways	STANDARD: BR3/S-P6B (available up to BR4/S-P8B)	available	/	available	available with volumetric control	available	available		INSTAL. (assemb): 3h, 2 people INSTAL. (in parts): 4h, 2 people START UP (assemb): 3h, 1 pers. START UP (in parts): 4h, 1 pers.	from 30 up to 60 useful days	radioactivity sensor: 20mm thick floor without necessity to crate it, slope finish	MINISTERIES, NUCLEAR POWER PLANTS, AIRPORTS
		noRADIO Plus	472	Automatic square cabin 180°, 90° right, 90° left	very high	1150 x 1150 x H 2222	700 x H 2000	850	DEMONTABLE	4-5 cycles one-way; 7-8 cycles two ways	STANDARD: BR3/S-P6B (available up to BR4/S-P8B)	available	/	available	available with volumetric control	available	available		INSTAL. (assemb): 3h, 2 people INSTAL. (in parts): 4h, 2 people START UP (assemb): 3h, 1 pers. START UP (in parts): 4h, 1 pers.	from 30 up to 60 useful days	radioactivity sensor: 20mm thick floor without necessity to crate it, slope finish	MINISTERIES, NUCLEAR POWER PLANTS, AIRPORTS
<b>demiCABINS</b>																						
demiCABINS		demiDUETTO	508	Automatic semi-round cabin with double sliding doors ready to be interlocked with manual door	medium	1380 x 930 x H 2304	900 x H 2090	500	DEMONTABLE	Doors opening speed: 1.5 s	STANDARD: P3A for sliding doors and BR1/S-P4B on sides (available up to BR2/S P6B)	available	/	NA	available with volumetric control	NA	available		INSTAL. (assemb): 3h, 2 people INSTAL. (in parts): 4h, 2 people START UP (assemb): 3h, 1 pers. START UP (in parts): 4h, 1 pers.	from 30 up to 60 useful days	it can be used to protect ATM machines: 12mm thick floor without necessity to crate it	BANKS, OFFICES, COMMERCIAL CENTRES, INDUSTRIES
		demiDUETTO Maxi	495	Automatic semi-round cabin with double sliding doors ready to be interlocked with automatic sliding door	medium	2300 x 1540 x H 2602	1050 X H 2400	760	ONLY IN PARTS	Doors opening speed: 2 s	STANDARD: P3A (available up to BR1/S-P4B)	available	/	NA	NA	NA	available		INSTAL.: 10h, 3 people START UP: 6h, 1 pers.	from 60 up to 90 useful days	no floor	BANKS, OFFICES, COMMERCIAL CENTRES, INDUSTRIES
		demiSELF	492	Automatic semi-round cabin with double sliding doors ready to be interlocked with manual door	medium	1380 x 930 x H 2214	850 x H 2000	600	DEMONTABLE	Door opening speed: 3 s	STANDARD: P3A (available up to BR1/S P4B)	available	/	NA	available with volumetric control	NA	available		INSTAL. (assemb): 3h, 2 people INSTAL. (in parts): 5h, 2 people START UP (assemb): 3h, 1 pers. START UP (in parts): 4h, 1 pers.	from 60 up to 90 useful days	it can be used to protect ATM machines: 12mm thick floor without necessity to crate it	BANKS, OFFICES, COMMERCIAL CENTRES, INDUSTRIES
<b>DOORS</b>																						
DOORS		COMPACT PLUS	935	Automatic double rototranslating door	medium	1422 x 445 x H 2276	1140 x H 2106	500	ONLY IN PARTS	door opening speed: from 2 up to 4s	STANDARD: P3A (available up to BR3/S-P6B)	available	available	NA	available when interlocked with another door	NA	available when interlocked with another door		INSTAL.: 6h, 3 people START UP: 3h, 1 pers.	from 30 up to 60 useful days	no floor: it can be used as emergency escape and as one/way corridor	BANKS, AIRPORTS, COMMERCIAL CENTRES, SHOPS
		COMPACT PLUS LIGHT	936	Automatic double unframed rototranslating door	medium	1422 x 445 x H 2276	1140 x H 2106	460	ONLY IN PARTS	door opening speed: from 2 up to 4s	STANDARD: P3A (available up to BR2/S-P6B)	available	available	NA	available when interlocked with another door	NA	available when interlocked with another door		INSTAL.: 6h, 3 people START UP: 3h, 1 pers.	from 30 up to 60 useful days	no floor: it can be used as emergency escape and as one/way corridor	BANKS, AIRPORTS, COMMERCIAL CENTRES, SHOPS
		COMPACT PLUS R	937	Automatic double reinforced rototranslating door	high	1422 x 445 x H 2276	1140 x H 2106	650	ONLY IN PARTS	door opening speed: from 3 up to 4s	STANDARD: BR2/S-P6B (available up to BR3/S-P6B)	available	available	NA	available when interlocked with another door	NA	available when interlocked with another door		INSTAL.: 6h, 3 people START UP: 3h, 1 pers.	from 30 up to 60 useful days	no floor: it can be used as emergency escape and as one/way corridor	BANKS, AIRPORTS, COMMERCIAL CENTRES, SHOPS
		SPEEDY	950	Automatic double swing door	low	1356 x 270 x H 2300	930 x H 2100	170	ONLY IN PARTS	door opening speed: 2s	STANDARD: 6/8 mm, laminated and tempered	NA	NA	NA	available when interlocked with another door	NA	available when interlocked with another door		INSTAL.: 6h, 3 people START UP: 3h, 1 pers.	from 60 up to 90 useful days	no floor: it can be used as emergency escape and as one/way corridor	BANKS, AIRPORTS, COMMERCIAL CENTRES, SHOPS